

Catalog #:	
Project :	
Type :	Date:
Notes:	

## TK-GBX3 Gimbal Spot

TK-GBX3 SERIES

### DESCRIPTION

TK-GBX3 Spot Gimbal comes complete with an Remote J-Box Isolated power supply. CRI90, 5CCT Selectable Tunable switch to adjust CCT output.

### APPLICATIONS

For new construction installation. Optional UL listed emergency battery pack



### QUICK SHIP :

TKGBX3-R03-9W-9SCT



### Specification Features

#### Controls / Dimming

120VAC, TRIAC 10-100% smooth dimming. 15/ 24 / 36 / 50° beam angle available. 30° tilt and 360° rotation. **Optional Features:** Flexible and interchangeable lenses (Leadtime required)

#### Warranty

5 Years Limited Warranty. See warranty documentation for more information.

#### Certification

It complies with ETL, FCC, ES and California Title 24.

#### Installation / Mounting

Easy installation. Spring-action housing clips. Optional UL listed emergency battery pack. Optional New construction pan or Joist pan installation

### Ordering Information

Example: TKGBX3-R02-5W-9SCT

TKGBX3	R02	5W	9SCT
<b>Brand</b>	<b>Series</b>	<b>Watts</b>	<b>5 Color Tunable</b>
TKGBX3 (Tektron)	2" = R02 (MTO) 3" = R03 (MTO) 4" = R04 (MTO)	5W - 5 Watts 9W - 9 Watts 14W - 14 Watts	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 50K - 5000K

### Specification Features

Input Voltage	120V 50 / 60 Hz
CCT	27000K-5000K
Luminous efficacy	350-1050Lm
CRI	>90
Dimmable	TRIAC 10-100%
Beam Angle	15/ 24 / 36 / 50°
LED Chip	COB
Life Span	50,000+ h

### Product Dimension

Part Number	D	H	Cut-out
TKGBX3-R02-5W-9SCT	2.55 inch	1.49 inch	2 inch
TKGBX3-R03-9W-9SCT	3.34 inch	1.57 inch	3 inch
TKGBX3-R04-14W-9SCT	5.03 inch	1.77 inch	4 inch