

Catalog:	
Project:	
Type:	Date:
Notes:	

Smart LED Vapor Tight / Tri- Proof Light

TK-ASTP™ Series

Description

TekTron's TK-ASTP Series is a smart LED light that has strong body and it can with stand harsh environments. It can be customized with sensors or IOT controllers at any time. It has a simple plug and play design that allows you to adjust the power and color temperature according to your needs. These LED lights are vapor tight and tri proof.

Applications

Ideal for lighting up supermarkets, pathways, storage units, stairwells and garages.



Quick Ship
TK-ASTP504TP50SR



Specification Features

Controls / Dimming

0-10V dimming option. Motion & daylight sensor, Zig-Bee Bluetooth, Wireless Daintree compliant options. IP65 Rated.

Certification

It complies with ETL Listings, DLC Premium, CE.

Warranty

5 Years Limited Warranty.
For more information visit us at, www.technoledlights.com/warrantyinfo

Installation / Mounting

The installation process is straight forward and offers a range of mounting possibilities with 1/2" NPT Pendant mount


Ordering Information Example: TK-ASTP504TP50SR

TK	A-STP	50	4T	P	50	SR	[Blank]	Options
Brand	Series	Watts	Fixture Length	Efficiency	Color Temp	Sensor/ Wireless	Voltage	Cord
TK - TekTron	ASTP - S Series Tri-proof Vapor-Tight	28 - 28Watts 40 - 40Watts 50 - 50Watts 65 - 65Watts 80 - 80Watts 110 - 110Watts	2T - 2FT 4T - 4FT 5T - 5FT 8T - 8FT	(OMIT) - Standard Efficiency, std; P - Premium Efficiency	30 - 3000K T - 40 - 4000K 50 - 5000K (Default) (Adjustable CCT Optional)	(OMIT)=None, std ; SR - Sensor pluggable MS01 - Motion Sensor Ft MS02 - Motion Sensor <40 Ft ZGOI - Zigbee Wireless control BTOI - bluetooth control	(OMIT): 120-277V, std 347 - 120-347V 480 - 200-480V Dimming DO- 0-10VDC, Dim down to OFF; DA - Dali (No External Control Wiring, std, contactsales if needed)	(OMIT): cable gland access (no cord, no plug), std , C3 - 3 ft cord C6 - 6 ft cord (Other length Optional) AO - Field Adjustable Light Output AC - Field Adjustable Color Temp EM - EM Emergency Backup SPT - Surge protector 10kv

Specification Features


Input Voltage	120-277 VAC
Color Temperature (CCT)	5000K
Luminous efficacy (Lm/W)	160 Lm/W
Color Rendering Index (CRI)	Ra>80
Dimmable	0-10V
Power Factor	>0.95
IP Rating	IP65
Operating Temperature	-30°C +~ 45°C
Life Span	50,000+ Hrs

Product Dimension



Part Number	A (Length)	B (Width)	C (Height)
TK-ASTP-4	47.2"	2.7"	3.3"
TK-ASTP-8	90.6"	2.7"	3.3"

Accessories (optional)



3 seconds easily plug-in



Smart LED Tri-proof Light

